




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01H 1/00	A1	(11) International Publication Number: WO 97/14939 (43) International Publication Date: 24 April 1997 (24.04.97)
(21) International Application Number: PCT/US96/14421 (22) International Filing Date: 5 September 1996 (05.09.96) (30) Priority Data: 08/544,347 17 October 1995 (17.10.95) US (71) Applicant: WESTINGHOUSE ELECTRIC CORPORATION [US/US]; 11 Stanwix Street, Pittsburgh, PA 15222-1384 (US). (72) Inventors: BEESON, Robert, James; 2129 Knollview Court, Oviedo, FL 32765 (US). TWERDOCHLIB, Michael; 877 Woodcrest Way, Oviedo, FL 32765 (US). KAIN, Jeffrey, Arthur; 1335 Secretariat Pl., Chuluota, FL 32766 (US). (74) Agents: PANIAN, Michael, G. et al.; Westinghouse Electric Corporation, 11 Stanwix Street, Pittsburgh, PA 15222-1384 (US).		(81) Designated States: CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: PASSIVE SENSOR FOR MONITORING VIBRATION OF A COMBUSTION TURBINE BLADE

**(57) Abstract**

A passive blade vibration monitor sensor (50) for determining an arrival time of a blade (52) of a combustion turbine during operation, the sensor (50) includes an optical lens (42) which receives infrared radiation generated by the blade (52) of the turbine and generates a sensor signal from the received infrared radiation, the sensor signal indicating an arrival time of the blade (52) of the combustion turbine. Target material (54) having an emissivity lower than the emissivity of the blade (52) may be placed on the blade (52) to enhance sensor sensitivity especially shrouded blade environments.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

- 1 -

PASSIVE SENSOR FOR MONITORING VIBRATION OF A COMBUSTION TURBINE BLADE

FIELD OF THE INVENTION

The present invention relates to sensors used to monitor the vibration of turbine rotor blades, in particular, combustion turbine blades.

5

BACKGROUND OF THE INVENTION

Turbine systems, such as those shown in Figures 1A and 1B, employ a pressurized low density gas to provide mechanical energy to blades 34 of a rotor. As the pressurized gas is expanded in a turbine, the rotor generates mechanical
10 energy in the form of torque on a shaft of the rotor via the blades 34 of the turbine rotor. Common gases used in turbine systems include atmospheric air (mainly nitrogen) and steam (H₂O).

In combustion turbines, 10 and 20, high pressure
15 ("HP") gas is heated by the combustion of fuel 32 before the entry of the gas into the turbine rotor section. As a consequence, the temperature of the HP gas is greatly elevated prior to passage along blades 34 of a rotor of a turbine 20. For example, the turbine 20 shown in figure 1B has an eight
20 stage axial compressor, combustion chamber, and three stage axial flow turbine. In this turbine 20, air is drawn in an air inlet 22 and compressed by the stator blades 24 and compressor blades 26. The compressed, HP air is heated in the combustion chamber 28 where fuel is added at the fuel inlet
25 32. The HP, high temperature air is passed along the blades 34 of the turbine causing rotation of the shaft 38 of the

- 2 -

turbine. Finally, the lower pressure, lower temperature air (gas) passes into the turbine exhaust 36.

In turbine 20, the air is heated to about 843°C prior to passage along the blades 34 of the turbine. During
5 the normal operation of this turbine 20, the speed of the shaft 38 of the turbine 20 is approximately 22,300 revolutions per minute ("RPM") (3,600 for power generation turbines). In commercial combustion turbines used for large scale power generation, the speed of the shafts of the turbines during
10 normal operation is approximately 3,600 RPM. Due to the extreme conditions placed on a turbine during normal loading, in particular, the extreme stress placed on the turbine blades 34 which provide the fulcrum for the rotation of the shaft 38 of a turbine, systems have been developed to monitor the
15 status of blades of a turbine rotor. In particular, blade vibration monitors ("BVM") have been developed to determine vibration levels of blades of turbine rotors during operation. See, for example, the BVM described in commonly assigned U.S. Pat. Nos. 4,573,358, 4,757,717, 4,922,757, 5,148,711,
20 4,887,468, and 4,896,537, incorporated herein by reference.

To determine the vibration level of turbine blades, BVM sensors measure blade arrival times for a row of blades. For example, turbine 20 has three rows of blades 34 and, thus, one or more BVM sensors may be used to measure the blade
25 arrival times for each row of blades. Based on the number of blades on a turbine rotor and the shaft rotation speed, exact blade arrival times can be determined. If the measured arrival time of a blade is early or late as compared to the expected arrival time, then the blade must be vibrating, i.e.,
30 the blade is displaced from its normal/nominal position due to vibration.

To measure the arrival time of a turbine rotor blade, BVM systems utilize sensors which generate a signal representative of the arrival time of a blade. The sensor
35 signal is further processed by BVM sensor signal conditioning equipment which generates a pulse signal having logical pulses representing the arrival times of blade. The logical pulse

- 3 -

signal is evaluated by BVM interpretation equipment which determines the vibration level of the blade.

Known BVM sensors include electrical, laser-based, microwave, acoustic, and capacitive sensors. Each of these
5 known sensors, however, is not desirable for use in combustion turbine ("CT") environments. In particular, electrical sensors measure blade arrival times by detecting changes in magnetic environment near the sensor as blades pass very close. Electrical sensors include reluctance sensors and eddy
10 current sensors. Reluctance sensors utilize a coil and a permanent magnet to detect changes in reluctance where the change in reluctance indicates the arrival of a blade. Eddy current sensors utilize an active coil which induces eddy currents on the surface of blades to determine the arrival of
15 blades.

These electrical sensors are not acceptable in the high temperature environment of combustion turbines because the copper wire of the sensors can not withstand the high temperature without expensive ceramic coating. In addition,
20 magnets fail in reluctance due to high temperature. In addition, these sensors have limited bandwidths, especially the eddy current sensors, and, thus, the accuracy of the measurements generated by these sensors is limited.

Laser based sensors employ two systems to determine
25 or measure the arrival times of a row of blades. One of the two systems includes a fiber optic cable having an end inserted in the turbine near the area of rotation of a row of blades. The other end of the fiber optic cable is attached to a laser. The fiber optic cable directs a laser beam
30 generated by the laser onto the tips or faces of the row of blades. A second system of the laser based sensor includes a photodetector which is also placed in the turbine near the area of rotation of the row of blades. The second system focuses the reflections of the radiation of the beam generated
35 by the laser off the row of blades onto the photodetector. The photodetector generates a signal indicating blade arrival or passing times based on the focused reflections of the beam.

- 4 -

Laser based sensors are also unacceptable in combustion turbine environments. First, laser systems are very sensitive to ambient temperature and thus have a limited long term application in combustion turbine environments. In addition, laser based sensors are expensive. The installation and maintenance of a laser based system is labor intensive, i.e., the initial setup and maintenance of the critical optical alignment between the laser and the fiber optics. Finally, in order to measure arrival times for more than one row of blades, multiple lasers or a complex optical multiplexing element are needed.

Acoustic sensors utilize transducers to measure the sound waves generated downstream by blades passing through gas expanding in a turbine. Acoustic sensors are also unacceptable in combustion turbine environments. Commercial transducers can not withstand the high temperature environment of combustion turbines. In addition, the sound waves generated by the blades are sensitive to the temperature of the turbine and load on the blades. Finally, acoustic sensors can not actually determine blade displacement from the sound waves generated by the blades of the turbine.

As a consequence, a need exists for an accurate, inexpensive, BVM sensor which can withstand the environment of combustion turbines. In detail, the sensor must be capable of measuring blade arrival times of turbine whose shaft rotation speed may range from 3,600 RPM to 22,300 RPM in combustion turbine environments.

SUMMARY OF THE INVENTION

An object of the present invention is to provide an accurate, inexpensive, BVM sensor which can withstand the environment of combustion turbines. In an exemplary embodiment, the BVM sensor includes an optical lens. The optical lens is configured to receive infrared radiation generated by a blade of a turbine. The optical lens generates a sensor signal representative of an arrival time of the blade based on the received infrared radiation. The optical lens

- 5 -

may also be configured to receive infrared radiation generated by a blade and target material on a tip of the blade of a turbine. Again, the optical lens generates a sensor signal representative of an arrival time of the blade. In this configuration, however, the signal is based on the infrared radiation generated by the blade and the target material on the tip of the blade. Ideally, the blade has a first emissivity and the target material has a second emissivity significantly different than the first emissivity of the blade. In addition, ideally the target material is a thermal barrier ceramic consisting essentially of eight percent Yttria stabilized Zirconia. There may also be layer of MCrAlY between the target material and tip of the blade to facilitate proper bonding.

In another embodiment of the invention, the sensor is configured to receive infrared radiation generated by a plurality of blades of a turbine. In this configuration, the sensor generates a sensor signal representative of arrival times of the plurality of blades based on the received infrared radiation.

The optical lens used in any embodiment of the invention may be a discrete or gradient index lens. In addition, the optical lens may be coupled to a fiber optic cable. Finally, several optical lenses may be used to determine arrival times of blades associated with different rows of a combustion turbine.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A (Prior Art) is a diagram of combustion turbine system.

FIG. 1B (Prior Art) is a cross-sectional view of a combustion turbine system.

FIG. 2 is an exemplary embodiment of BVM system according to the present invention.

FIG. 3A is a graph of a signal generated by an exemplary BVM sensor from infrared radiation emitted from a

- 6 -

blade without target material according to the present invention.

FIG. 3B is a graph of a signal generated by an exemplary BVM sensor from infrared radiation emitted from a blade with target material according to the present invention.

FIG. 3C is a graph of a signal generated by exemplary BVM sensor signal conditioning equipment according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 2 illustrates a BVM system 40 according to the present invention. The system 40 includes BVM sensor 50 and BVM sensor signal conditioning equipment 46. A signal generated by the conditioning equipment 46 is processed by known BVM interpretation equipment (not shown) to generate vibration levels. In the exemplary embodiment of the invention, the BVM sensor 50 includes an optical focusing lens 42 and fiber optic cable 44 coupled to the focusing lens 42. This exemplary embodiment of the BVM sensor 50 also includes passive light-emitting targets 54 with an emissivity significantly different than the blade material attached to blade tips 52. In the exemplary body of the invention, the targets 54 emit less infrared radiation than the blades 52.

As noted above, in a combustion turbine high temperature, HP gas is passed over the blades of a turbine rotor. In the exemplary embodiment of the invention, the gas heats up both the blades 52 and targets 54 affixed to the blades. Both the targets 54 and blades 52 emit infrared radiation of a predictable power spectrum based on their ambient temperature and material composition. The optical lens 42 is oriented along a row of blades in a turbine. As a blade 52 with a target 54 passes the optical lens 42, the blade 52 and target 54 emit infrared radiation of a different intensity due to their differing emissivity. The optical lens 42 is configured to transmit the radiation produced by the blade 52 and target 54.

- 7 -

In particular, the optical lens 42 is configured so that enough radiation is received from the blade 52 and target 54 to insure accurate arrival time measurement. In addition, the optical lens 42 is configured so that only one blade 52 and target 54 is in the field of view of the lens at any time. As noted above, in the exemplary embodiment, the lens is configured to transmit the infrared radiation produced by the blades 52 and targets 54. In another embodiment, the optical lens 42 may be configured to transmit the infrared radiation only generated by the tips of the blades 52 of a turbine rotor, thus, eliminating the need for targets 54. In the exemplary embodiment of the invention, the optical lens 42 may be a discrete or gradient index lens. Regardless, the optical lens 42 couples the infrared radiation emitted from either the hot turbine blade 52 tips or combination of blade 52 tips and target material 54 into the optical fiber 44.

Figure 3A is a diagram of the optical signal produced by the optical lens 42 when a hot blade tip without target material passes into the field of view of the lens. The peak or center portion of the signal indicates when the blade 52 tip is centered in the field of view of the lens 42. As the temperature of the blades 52 increases, the energy level of its radiation also increases. As a consequence, the BVM sensor 42 will generate sensor signals with greater intensity and, thus, accuracy, as the temperature of the turbine system increases. Combustion turbines blades are commonly manufactured from a nickel based material which has a relatively high emissivity. The emissivity is approximately 0.7 to 0.8 on a scale from 0.0 to 1.0. Thus, the blades 52 will emit a relatively high level of radiant thermal energy for a given temperature.

In combustion turbine systems with tip shrouded turbine blades 52, a piecewise continuous outer shroud ring is typically formed by shroud segments at the tip of each blade. Unlike freestanding turbine blades, this outer shroud ring may not have sufficient geometrical discontinuities corresponding to each individual blade which are needed to

- 8 -

produce a measurable change in infrared radiation each time a blade passes a sensor 42. In order to facilitate BVM detection of such tip shrouded turbine blade configurations, a target 54, made from material possessing a measurably different emissivity from that of the outer shroud segment, is applied to the outer shroud segment of each blade.

As noted above, combustion turbine blades have a relatively high emissivity. Therefore, target material 54 with an emissivity significantly lower than the emissivity of the blades 52 is selected in order to generate a measurably different emissivity as each blade 52 passes the sensor 42. In operation, when a blade tip 52 with target material 54 passes the sensor 42 of the invention, a reduced level of infrared radiation is received and the reduction is used to determine or indicate the arrival or passing of a turbine blade 52. Figure 3B is a diagram of an optical signal produced by the optical lens 42 when a hot blade tip 52 with a target material 54 having an emissivity lower than the emissivity of the blade 52 (and shroud) passes into the field of view of the lens. The valley of the signal indicates when the target material 54 on the blade tip 52 is centered in the field of view of the lens 42. As the temperature of the combustion turbine increases, the differential between the energy level of radiation emitted by the target material 54 and the remainder of the system (blades tips and shrouding) increases. As a consequence, the BVM sensor 42 will generate sensor signals with greater accuracy as the temperature of the turbine system increases. It is noted that target material 54 may also be used in combustion turbine systems without shrouded blades. A signal similar to the signal shown in Figure 3B would be generated by a non-shrouded turbine blade system due to the difference in emissivity between the blade tips 52 of the system and target material 54.

In the preferred embodiment of the invention, the target material 54 is thermal barrier ceramic ("TBC") which is coated on tips of blades 52. The TBC is placed on an appropriate surface of each blade tip 52 to be monitored. A

- 9 -

preferred TBC is an eight percent Yttria stabilized Zirconia. In addition, a coating of MCrAlY is preferably placed between the eight percent Yttria stabilized Zirconia and blade surface 52 to facilitate proper bonding between surface of the blade tip 52 and TBC. The TBC has an emissivity of about 0.4%. As noted above, nickel based metal has an emissivity of about 0.7 to 0.8%. This differential in emissivity (0.4% versus 0.7 to 0.8%) is the source of the valley shown in Figure 3B.

The sensor signal or optical signal generated by the optical lens 42 (such as shown in Figures 3A and 3B) and coupled into the fiber optic cable 44 is processed by BVM sensor signal conditioning equipment 46 and BVM interpretation equipment. The BVM sensor signal conditioning equipment 46 and BVM interpretation equipment may be any type of known processing circuitry capable of extracting vibration information from an input signal representative of blade passing events as disclosed, for example, in the above mentioned U.S. Pat. Nos. 4,573,358, 4,757,717, 4,922,757, 5,148,711, 4,887,468, and 4,896,537.

Note, the BVM sensor 42 may also be used to generate other information, such as the temperature of the blade and target material, based upon the intensity of the sensor signal. Due to the use of the fiber optic cable 44, the BVM sensor signal conditioning equipment 46 and BVM interpretation equipment may be positioned far from the hot temperature environment of the combustion turbine. Thus, the BVM sensor 42 of the present invention helps prevent damage to and permits easy repair of the BVM sensor signal conditioning equipment 46 and BVM interpretation equipment.

As noted earlier, the BVM sensor signal conditioning equipment 46 converts the sensor signal into a logical pulse signal. The logical pulse signal is compatible with standard BVM interpretation equipment (such as equipment described in the above incorporated patents) where the standard BVM interpretation equipment generates vibration levels based upon the logical pulse signal. In the preferred embodiment of the invention, the BVM sensor signal conditioning equipment 46

- 10 -

includes a pyrometer. The pyrometer replaces zero crossing detectors used in known signal conditioning equipment, such as the equipment described in the incorporated patents. The pyrometer could also be replaced with a reference level
5 detector as described in the incorporated patents. The signal conditioning equipment 46, thus, acts as a transducer taking infrared pulses generated by the BVM sensor 50 and generating logical pulse signals. In systems employing target material
10 54, the BVM sensor signal conditioning equipment 46 generates logical pulse signal for each valley in the signal. Figure 3C is a graph of a logical pulse signal generated by BVM sensor signal conditioning equipment 46 according to the present invention.

For systems not employing target material 54, the
15 pulse is centered on the rising edge of the sensor signal (such as shown in Figure 3A). The pulse indicates the exact time arrival of a blade tip 52. For systems employing target material 54, the pulse is centered at the falling edge of the sensor signal (such as shown in Figure 3B). The pulse thus
20 indicates the exact time arrival of target material 54 on a blade tip 52. A string or time series of the logical pulses are processed by BVM interpretation equipment to determine the vibration levels of blades of the system.

As noted above, a turbine system may have more than
25 one row of blades. In the present invention, a separate optical lens 42 coupled to a fiber optic cable 44 may be aligned over each of the rows of blades of a turbine. One or multiple BVM sensor signal conditioning equipment 46 may be used to generate logical pulse signals for each of the rows
30 of blades. Then, standard BVM interpretation equipment may be used to determine the vibration levels of each row of blades of a turbine system.

Although the invention has been described in terms of an exemplary embodiment, the spirit and scope of the
35 appended claims are unlimited by any details not expressly stated in the claims.

-11-

What is Claimed is:

1. A blade vibration monitor (BVM) sensor for generating a sensor signal representative of an arrival time of a blade of a turbine rotor during the rotation of the turbine, the BVM sensor comprising an optical lens configured
5 to receive infrared radiation generated by the blade of the turbine rotor and to generate the sensor signal representative of the arrival time of the blade based on the infrared radiation.

2. A blade vibration monitor (BVM) sensor
10 according to claim 1, wherein the optical lens is configured to receive infrared radiation generated by the blade and target material on a tip of the blade of the turbine rotor and to generate the sensor signal representative of the arrival time of the blade based on the infrared radiation generated
15 by the blade and the target material.

3. A blade vibration monitor (BVM) sensor according to claim 1, wherein the optical lens is one of a discrete lens and a gradient index lens.

4. A blade vibration monitor (BVM) sensor
20 according to claim 1, further comprising a fiber optic cable coupled to the optical lens and signal conditioning equipment coupled to the fiber optic cable.

- 12 -

5. A combustion turbine for generating electricity, the turbine comprising:

a turbine rotor having a plurality of blades; and
an optical lens coupled with the turbine rotor and
5 configured to receive infrared radiation generated by the plurality of blades of the turbine rotor and to generate a sensor signal representative of arrival times of the plurality of blades based on the infrared radiation.

6. A combustion turbine according to claim 5,
10 wherein the optical lens is configured to receive infrared radiation generated by the plurality of blades and target material on tips of each of the plurality of blades of the turbine rotor and to generate the sensor signal representative of the arrival times of the plurality of blades based on the
15 infrared radiation generated by the blades and the target material.

7. A combustion turbine according to claim 5, wherein the optical lens is one of a discrete lens and a gradient index lens.

8. A combustion turbine according to claim 5,
20 further comprising a fiber optic cable coupled to the optical lens and signal conditioning equipment coupled to the fiber optic cable.

9. A combustion turbine according to claim 5,
25 wherein the optical lens is configured to have a limited field of view so that radiation is received from primarily only one of the plurality of blades at any point in time.

- 13 -

10. A combustion turbine for generating electricity, the turbine comprising:

a turbine rotor having a plurality of blades;

an optical lens coupled with the turbine rotor and
5 configured to receive infrared radiation generated by the plurality of blades and target material on tips of each of the plurality of blades of the turbine rotor, to generate a sensor signal representative of arrival times of the plurality of blades based on the infrared radiation generated by the blades
10 and target material, and to have a limited field of view so that infrared radiation is received from primarily only one of the plurality of blades and the target material on the tip of the blade at any point in time, the optical lens being one of a discrete lens and a gradient index lens;

15 a fiber optic cable coupled to the optical lens; and signal conditioning equipment coupled to the fiber optic cable where the signal conditioning equipment generates a logical pulse signal from the sensor signal generated by the optical lens.

20 11. A passive blade vibration monitor (BVM) sensor for generating a sensor signal representative of arrival times of a plurality of blades of a turbine rotor during the rotation of the turbine, the BVM sensor comprising an optical lens configured to receive infrared radiation generated by the
25 blades of the turbine rotor, to generate the sensor signal representative of arrival times of the plurality of blades based on the infrared radiation generated by the blades, and to have a limited field of view so that radiation is received from primarily only one of the plurality of blades at any
30 point in time.

- 14 -

12. A passive blade vibration monitor (BVM) sensor according to claim 11, wherein the optical lens is configured to receive infrared radiation generated by the plurality of blades and target material on tips of the plurality of blades
5 of the turbine rotor and to generate the sensor signal representative of the arrival times of the plurality of blades based on the infrared radiation generated by the blades and target material.

13. A passive blade vibration monitor (BVM) sensor
10 according to claim 11, wherein the optical lens is one of a discrete lens and a gradient index lens and further comprising a fiber optic cable coupled to the optical lens and signal conditioning equipment coupled to the fiber optic cable.

- 15 -

14. A passive blade vibration monitor (BVM) for generating a logical pulse signal representative of arrival times of a plurality of blades of a turbine rotor during the rotation of the turbine, the BVM comprising:

5 a target attached to a tip of each of the plurality of blades of the turbine rotor; and

 an optical lens configured to receive infrared radiation generated by the plurality of blades and the targets attached to the tips of the plurality of blades of the turbine
10 rotor, to generate a sensor signal representative of arrival times of the plurality of blades based on the infrared radiation generated by the plurality of blades and targets attached to the tips of the plurality of blades, and to have a limited field of view so that radiation is received from
15 primarily only one of the plurality of blades and the target attached to the tip of the blade at any point in time, the optical lens being one of a discrete lens and a gradient index lens;

 a fiber optic cable coupled to the optical lens; and
20 signal conditioning equipment coupled to the fiber optic cable where the signal conditioning equipment generates the logical pulse signal from the sensor signal generated by the optical lens.

- 16 -

15. A combustion turbine for generating electricity, the turbine comprising:

a turbine rotor having a first plurality of rows, each of the rows having a second plurality of blades; and

5 a first plurality of optical lens coupled with the turbine rotor so as to be aligned with each of the first plurality of rows,

each of the first plurality of optical lens configured to receive infrared radiation generated by the
10 second plurality of blades of a corresponding one of the first plurality of rows of the turbine rotor and to generate a sensor signal representative of arrival times of the second plurality of blades of the corresponding one of the first plurality of rows based on the infrared radiation.

15 16. A combustion turbine according to claim 15, wherein the first plurality of optical lens are configured to receive infrared radiation generated by the second plurality of blades and target material on tips of each of the second plurality of blades of the corresponding one of the first
20 plurality of rows of the turbine rotor and to generate the sensor signal representative of the arrival times of the second plurality of blades of the corresponding one of the first plurality of rows based on the infrared radiation generated by the blades and target material.

25 17. A combustion turbine according to claim 16, wherein each of the first plurality of optical lens is one of a discrete lens and a gradient index lens.

- 17 -

18. A combustion turbine according to claim 17,
further comprising a first plurality of fiber optic cables
coupled to the first plurality of optical lens and signal
conditioning equipment coupled to the first plurality of fiber
5 optic cables where the signal conditioning equipment generates
logical pulse signals from the sensor signals generated by the
plurality of optical lens.

19. A combustion turbine according to claim 18,
wherein each of the first plurality of optical lens is
10 configured to have a limited field of view so that radiation
is received from primarily only one of the second plurality
of blades of the corresponding one of the first plurality of
rows at any point in time.

- 18 -

20. A combustion turbine for generating electricity, the turbine comprising:

a turbine rotor having a first plurality of rows, each of the rows having a second plurality of blades;

5 a first plurality of optical lens coupled with the turbine rotor so as to be aligned with each of the first plurality of rows,

each of the first plurality of optical lens configured to receive infrared radiation generated by the
10 second plurality of blades and target material on tips of each of the second plurality of blades of the corresponding one of the first plurality of rows of the turbine rotor, to generate a sensor signal representative of the arrival times of the second plurality of blades of the corresponding one of the
15 first plurality of rows based on the infrared radiation generated by the blades and target material, and to have a limited field of view so that radiation is received from primarily only one of the second plurality of blades and the target material on the tip of the one of the second plurality
20 of blades of the corresponding one of the first plurality of rows at any point in time, each of the first plurality of optical lens being one of a discrete lens and a gradient index lens;

a first plurality of fiber optic cables coupled to
25 the first plurality of optical lens; and

signal conditioning equipment coupled to the first plurality of fiber optic cables where the signal conditioning equipment generates logical pulse signals from the sensor signals generated by the first plurality of optical lens.

- 19 -

21. A blade vibration monitor (BVM) sensor for generating a sensor signal representative of an arrival time of a blade of a turbine rotor during the rotation of the turbine, the blade having a first emissivity and the BVM
5 sensor comprising:

target material on a tip of the blade, the target material having a second emissivity lower than the first emissivity of the blade; and

an optical lens configured to receive infrared
10 radiation generated by the blade and the target material on the tip of the blade of the turbine rotor and to generate the sensor signal representative of the arrival time of the blade based on the infrared radiation generated by the blade and the target material.

15 22. A blade vibration monitor (BVM) sensor according to claim 21, wherein the target material is a thermal barrier ceramic.

23. A blade vibration monitor (BVM) sensor according to claim 22, wherein the target material consists
20 essentially of about eight percent Yttria stabilized Zirconia.

24. A blade vibration monitor (BVM) sensor according to claim 23, further comprising a layer of MCrAlY beneath the layer of target material on the tip of the blade.

- 20 -

25. A blade vibration monitor (BVM) sensor for generating a sensor signal representative of an arrival time of a blade of a turbine rotor during the rotation of the turbine, the blade having a first emissivity and the BVM
5 sensor comprising:

target material consisting essentially of about eight percent Yttria stabilized Zirconia on a tip of the blade, the target material having a second emissivity lower than the first emissivity of the blade;

10 a layer of MCrAlY beneath the layer of target material on the tip of the blade;

an optical lens configured to receive infrared radiation generated by the blade and the target material on the tip of the blade of the turbine rotor and to generate the
15 sensor signal representative of the arrival time of the blade based on the infrared radiation generated by the blade and the target material, wherein the optical lens is one of a discrete lens and a gradient index lens;

a fiber optic cable coupled to the optical lens; and
20 signal conditioning equipment coupled to the fiber optic cable.

- 21 -

26. A combustion turbine comprising:

a turbine rotor having a plurality of shrouded blades, the plurality of blades having a first emissivity;

5 target material on a tip of at least one of the plurality of blades, the target material having a second emissivity lower than the first emissivity of the plurality of blades;

10 an optical lens configured to receive infrared radiation generated by the at least one of the plurality of blades and the target material on the tip of the at least one of the plurality of blades of the turbine rotor and to generate the sensor signal representative of the arrival time of the at least one of the plurality of blades based on the infrared radiation generated by the at least one of the
15 plurality of blades and the target material, wherein the optical lens is one of a discrete lens and a gradient index lens;

a fiber optic cable coupled to the optical lens; and
20 signal conditioning equipment coupled to the fiber optic cable.

27. A blade vibration monitor (BVM) sensor according to claim 26, wherein the target material is a thermal barrier ceramic.

28. A blade vibration monitor (BVM) sensor
25 according to claim 27, wherein the target material consists essentially of about eight percent Yttria stabilized Zirconia.

29. A blade vibration monitor (BVM) sensor according to claim 28, further comprising a layer of MCrAlY beneath the layer of target material on the tip of the blade.

- 22 -

30. A combustion turbine comprising:

a turbine rotor having a plurality of shrouded blades, the plurality of blades having a first emissivity;

target material consisting essentially of about
5 eight percent Yttria stabilized Zirconia on a tip of the at least one of the plurality of blades, the target material having a second emissivity lower than the first emissivity of the plurality of blades;

a layer of MCrAlY beneath the layer of target
10 material on the tip of the at least one of the plurality of blades;

an optical lens configured to receive infrared radiation generated by the at least one of the plurality of blades and the target material on the tip of the at least one
15 of the plurality of blades of the turbine rotor and to generate the sensor signal representative of the arrival time of the at least one of the plurality of blades based on the infrared radiation generated by the at least one of the plurality of blades and the target material, wherein the
20 optical lens is one of a discrete lens and a gradient index lens;

a fiber optic cable coupled to the optical lens; and
signal conditioning equipment coupled to the fiber optic cable.

- 23 -

31. A passive blade vibration monitor (BVM) for generating a logical pulse signal representative of arrival times of a plurality of shrouded blades of a turbine rotor during the rotation of the turbine, the plurality of blades
5 having a first emissivity, the BVM comprising:

target material attached to a tip of each of the plurality of blades of the turbine rotor, the target material having a second emissivity lower than the first emissivity of the plurality of blades; and

10 an optical lens configured to receive infrared radiation generated by the plurality of blades and the target material attached to the tips of the plurality of blades of the turbine rotor, to generate a sensor signal representative of arrival times of the plurality of blades based on the
15 infrared radiation generated by the plurality of blades and the target material attached to the tips of the plurality of blades, and to have a limited field of view so that radiation is received from primarily only one of the plurality of blades and the target material attached to the tip of the blade at
20 any point in time, the optical lens being one of a discrete lens and a gradient index lens;

a fiber optic cable coupled to the optical lens; and
signal conditioning equipment coupled to the fiber optic cable where the signal conditioning equipment generates
25 the logical pulse signal from the sensor signal generated by the optical lens.

32. A blade vibration monitor (BVM) sensor according to claim 31, wherein the target material is a thermal barrier ceramic.

30 33. A blade vibration monitor (BVM) sensor according to claim 32, wherein the target material consists essentially of about eight percent Yttria stabilized Zirconia.

- 24 -

34. A blade vibration monitor (BVM) sensor according to claim 33, further comprising a layer of MCrAlY beneath the layer of target material on the tip of the blade.




FIG. 1A
PRIOR ART




FIG. 2

2/3







FIG. 1B
PRIOR ART

3/3

*FIG. 3A**FIG. 3B**FIG. 3C*

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 96/14421

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G01H1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G01H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	SENSORS AND ACTUATORS A, vol. A32, no. 1 / 03, 1 April 1992, pages 539-542, XP000287371 ANDRENELLI L ET AL: "LARGE-BANDWIDTH REFLECTION FIBER-OPTIC SENSORS FOR TURBOMACHINERY ROTOR BLADE DIAGNOSTICS" see figures 1,2	1,3,4
A	US,A,5 201 227 (IINUMA HIDEYASU ET AL) 13 April 1993 see column 2, line 5 - line 17; figure 1	1
A	US,A,4 914 953 (VISOVICH PAUL W) 10 April 1990 see abstract; figure 2	1,2
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

12 December 1996

Date of mailing of the international search report

20. 12. 96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Anderson, A

INTERNATIONAL SEARCH REPORT

In. ional Application No
PCT/US 96/14421

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 408 827 (GUTHRIE RICHARD W ET AL) 11 October 1983 see column 1, line 36 - line 55 see column 2, line 47 - line 57; figure 1 ---	1
A	US,A,4 757 717 (WOLFINGER JOHN F ET AL) 19 July 1988 cited in the application ---	
A	US,A,4 573 358 (LUONGO MICHAEL C) 4 March 1986 cited in the application ---	
A	US,A,4 896 537 (OSBORNE ROBERT L) 30 January 1990 cited in the application ---	
A	US,A,4 887 468 (MCKENDREE FRANCIS S ET AL) 19 December 1989 cited in the application ---	
A	US,A,5 148 711 (TWERDOCHLIB MICHAEL ET AL) 22 September 1992 cited in the application ---	
A	US,A,4 922 757 (ROZELLE PAUL F ET AL) 8 May 1990 cited in the application -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/US 96/14421

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-5201227	13-04-93	EP-A- 0558843	08-09-93
US-A-4914953	10-04-90	CA-A- 2002280 JP-A- 2171618	07-05-90 03-07-90
US-A-4408827	11-10-83	NONE	
US-A-4757717	19-07-88	NONE	
US-A-4573358	04-03-86	CA-A- 1234201 EP-A- 0179618 JP-C- 1766141 JP-B- 4054803 JP-A- 61101605 KR-B- 9410053	15-03-88 30-04-86 11-06-93 01-09-92 20-05-86 21-10-94
US-A-4896537	30-01-90	CA-A- 1331491 CN-A- 1039114 JP-A- 2023208	16-08-94 24-01-90 25-01-90
US-A-4887468	19-12-89	CA-A- 1329848 CN-A- 1039111 JP-A- 2027103	24-05-94 24-01-90 29-01-90
US-A-5148711	22-09-92	CA-A- 2054598 ES-B- 2038918 IT-B- 1251959 JP-A- 4362206	02-05-92 16-01-95 27-05-95 15-12-92
US-A-4922757	08-05-90	CN-A- 1038700 JP-A- 2103423	10-01-90 16-04-90